

DUPLEX CAMERA PORTABLE MOTION CAPTURE SYSTEM FOR SINGLE  
ATHLETE'S PERFORMANCE ANALYSIS

MUHAMMAD ZULHILMI BIN KAHARUDDIN

A project submitted in partially fulfilment of requirement for the award of the Degree  
of Master of Mechanical Engineering

Faculty of Mechanical and Manufacturing Engineering

University Tun Hussein Onn Malaysia

MARCH 2020

## ACKNOWLEDGEMENT

I gratefully acknowledge who has supported me throughout my Master work and finally the preparation of this thesis. I would like to thank my supervisor, Associate Prof. Dr Zamani bin Ngali, for accepting me as a student, whilst I am not an excellent student. Dr, many thanks for your relentless commitment you have shown along this journey even at the same time you have other commitments as Deputy Dean of student affairs and alumni. You always have patient in guiding me even though my research progress is quite slow. I will always remember and look to you as an example of how to work hard! I would also like to thank Wee Chang Ann for insightful guidance of my research studies. All your effort shows me the real meaning of sincerity!

I would like to thank all the great friends I have had at Universiti Tun Hussein Onn Malaysia (UTHM). Thank you all for providing many happy memories and truly friendship colours. I wish to thank my sponsors, Grant FRGS 1543 under Minister of Higher Education Malaysia. I must also thank to Faculty of Mechanical and Manufacturing and Perwira Residential College members.

I would achieve nothing without the encouragement and compassion I received from my understanding parent and all my families. This thesis is dedicated to them. Their love and support kept me going. I am grateful!

## ABSTRACT

In recent years, introduction of depth camera in motion capture have caught a massive attention by both researchers and biomechanists. Therefore, high-performance sports certainly require motion capture technology to compete with other competitors. Thus, a study involving quantitative analysis is important to obtain a more accurate analysis. The purpose of this study is to develop duplex motion capture system for biomechanical analysis of sports. The visual sensor used in this research consists of two Kinect sensors Microsoft. The case studies were focused on a single athlete for sepak takraw pre-serve and bunga silat at any single time. MATLAB and Software Development Kit (SDK) by Microsoft were used as software developing platform. Accuracy between software developed in MATLAB platform and SDK were compared and the best platform in term of performance and accuracy were chosen. “Bunga silat” in Silat and sepak takraw pre-serve were chosen as the case studies to justify the feasibility of the system. This study also examined the capability of Kinect Xbox 360° sensor and software to be used in biomechanical analysis. Result obtained revealed significant achievement in terms of motion capture system in the biomechanical analysis on certain sports. For Sepak Takraw, the foot-to-foot distance and angle of knee before serve has been used as a parameter to determine the speed of the ball to be serviced. In this research the highest ball speed recorded is 69km/h with 1.0664m of foot-to-foot distance and 147.20° of right knee 153.52° for the left knee at the pre-serve phase. Whereas for Silat, it shows that the amateur motion is very much similar from the practitioners. The closer the mean and standard deviation value to unity the more accurate the movement referred to the benchmark stated. Therefore, to increase the accuracy of movement execution, the subject needs to repeat the movement execution until perfection which is set by the teacher. In summary, this research successfully described an athlete’s performance quantitatively using motion capture system.

## ABSTRAK

Dalam tahun kebelakangan ini, pengenalan kamera kedalaman dalam penangkapan pergerakan telah menarik perhatian besar para penyelidik dan biomekanik. Oleh itu, sukan berprestasi tinggi memerlukan teknologi menangkap gerakan untuk bersaing dengan pesaing lain. Kajian yang melibatkan analisis kuantitatif adalah penting untuk mendapatkan analisis yang lebih tepat. Tujuan kajian ini adalah untuk membangunkan sistem tangkapan gerakan jenis dupleks untuk analisis biomekanikal terhadap sukan. Visual pengesan yang digunakan dalam kajian ini terdiri daripada dua Pengesan Kinect Microsoft. Kajian kes difokuskan pada atlet tunggal untuk pra-servis sepak takraw dan bunga silat pada satu-satu masa. MATLAB dan Kit Pembangunan Perisian (SDK) oleh Microsoft telah digunakan sebagai platform pembangunan perisian. Ketepatan antara perisian MATLAB dan SDK telah dibandingkan dan perisian terbaik dari segi kualiti dan ketepatan telah dipilih. "Bunga silat" dalam Silat dan sepak takraw pra-servis dipilih sebagai kajian kes untuk membenarkan kelayakan sistem ini. Kajian ini juga menilai keupayaan pengesan Kinect Xbox 360° dan perisian untuk digunakan dalam analisis biomekanik. Keputusan yang diperolehi menunjukkan pencapaian yang ketara dari segi sistem tangkapan pergerakan dalam analisis biomekanik pada sukan tertentu. Untuk Sepak Takraw, jarak kaki dan sudut lutut sebelum melakukan servis telah digunakan sebagai parameter untuk menentukan kelajuan bola untuk diservis. Kelajuan bola tertinggi yang direkodkan adalah 69km/j dengan jarak 1.0664m kaki ke kaki dan 147.20 ° lutut kanan 153.52 ° untuk lutut kiri pada fasa pra-servis. Nilai min untuk kelajuan bola ialah 57.2km/j. dan penyimpangan standard adalah 8.87km/j. Silat pula menunjukkan bahawa gerakan dari amatir sangat mirip dengan para pengamal. Lebih dekat nilai min dan nilai sisihan piawai untuk perpaduan lebih tepat pergerakan merujuk kepada tanda aras yang dinyatakan. Oleh itu, untuk meningkatkan ketepatan pelaksanaan pergerakan, subjek perlu mengulangi pergerakan hingga sempurna seperti yang ditetapkan oleh jurulatih. Ringkasnya, penyelidikan ini berjaya menggambarkan prestasi atlit secara kuantitatif

## TABLE OF CONTENTS

<b>DECLARATION</b>	<b>ii</b>
<b>ACKNOWLEDGEMENT</b>	<b>iii</b>
<b>ABSTRACT</b>	<b>iv</b>
<b>TABLE OF CONTENTS</b>	<b>vi</b>
<b>LIST OF TABLES</b>	<b>x</b>
<b>LIST OF FIGURES</b>	<b>xii</b>
<b>LIST OF SYMBOLS AND ABBREVIATIONS</b>	<b>xvi</b>
<b>LIST OF APPENDICES</b>	<b>xviii</b>
 <b>CHAPTER 1 INTRODUCTION</b>	 <b>1</b>
1.1 Overview	1
1.2 Background of Study	2
1.3 Problem Statement	2
1.4 Objectives	3
1.5 Scope	4
1.6 Significance of study	4
 <b>CHAPTER 2 LITERATURE REVIEW</b>	 <b>5</b>
2.1 Introduction	5
2.2 Biomechanics	5
2.2.1 Kinematics and Kinetic Motion	6
2.3 The concept of Biomechanical Analysis	6
2.3.1 Qualitative Analysis	7
2.3.2 Quantitative Analysis	8

2.4	Motion Capture (MoCap) System	9
2.4.1	Marker-less MoCap System	10
2.4.2	Kinect System	11
2.4.2.1	Coordinate Spaces	12
2.5	Accuracy of Kinect System	13
2.6	Previous Works	15
2.7	Kinect Skeleton Data	18
2.8	Research Case Studies	20
2.8.1	<i>Sepak Takraw</i> Pre-Serve	20
2.8.1.1	<i>Sepak Takraw</i> Server Tekong	21
2.8.1.2	Trigonometry Function	22
2.8.2	Silat	23
2.8.2.1	Biomechanical Analysis Used in Martial Arts Analysis	24

### **CHAPTER 3      METHODOLOGY      25**

3.1	Introduction	25
3.2	Stages of Methodology	25
3.3	Identification of Problem Statements, Objectives and Scope of Study	27
3.4	Development of Duplex-Kinect System and Calibration	27
3.5	Data Acquisition from Kinect Sensor	29
3.6	Skeleton Fusion	30
3.7	Verification of Experiment Setup	34
3.8	Accuracy Validation of SDK and MATLAB	38
3.9	Biomechanical Analysis on the Athlete's Performance	39
3.9.1	Biomechanical Analysis on the Sepak Takraw Tekong Athlete's Performance	39
3.9.2	Biomechanical Analysis on the Silat Athlete's Performance	51

<b>CHAPTER 4</b>	<b>EXPERIMENTAL RESULTS AND ANALYSIS</b>	<b>57</b>
4.1	Analysis of the Duplex Kinect System Performance	57
4.1.1	Body Posture Joint Index	57
4.1.2	Sample Profile for SDK and MATLAB Experiment	58
4.1.3	Summary	64
4.2	Sepak Takraw (Pre-Serve) Result and Discussion	65
4.2.1	Tekong Sample Profile	65
4.2.2	Serve Technique Parameter	65
4.2.3	Simplifying Skeleton Model	68
4.2.4	Analysis on Simplified Model	69
4.2.5	Foot-to-Foot Euclidean Distance at Pre-Serve Phase	69
4.2.6	Calculating Foot-to-Foot Distance when Given 2 Set 3D (x,y,z) Coordinates	69
4.2.7	Relative Angle for Right Knee ( $A^\circ$ ) at Extension (Pre-Serve Phase)	72
4.2.8	Relative Angle for Left Knee ( $B^\circ$ ) at Extension (Pre-Serve Phase)	76
4.2.9	Summary	79
4.2.10	Foot-to-Foot Distance	80
4.2.11	Knee Angle	80
4.3	Silat Result and Discussion	82
4.3.1	Silat Practitioners' Profile	82
4.3.2	Components of Jurus Satu	83
4.3.3	Analysis Joints per Movement	87
4.3.4	Joint Displacement per Movement of 'Jurus Satu'	89
4.3.5	Joint Velocity per Movement of 'Jurus Satu'	90
4.3.6	Joint Acceleration per Movement of 'Jurus Satu'	92

4.3.7	Result and Discussion Summary	93
4.3.7.1	Joint Displacement	94
4.3.7.2	Joint Velocity	96
4.3.7.3	Joint Acceleration	98
4.4	Overall Analysis Summary	99
<b>CHAPTER 5</b>	<b>CONCLUSION AND FUTURE WORK</b>	104
5.1	Overview	104
5.2	Achievement	106
5.3	Limitations	106
5.4	Future Work	107
	<b>REFERENCES</b>	108
	<b>APPENDICES</b>	113



PT TA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH



## LIST OF TABLES

3.1	Joint selection logic for duplex Kinect system	33
3.2	List of apparatus and equipment for Sepak Takraw Pre-Serve experiment	43
4.1	The bone length obtained via MatLab	59
4.2	The bone length obtained via SDK	60
4.3	Foot to foot Euclidean distance data tabulation	70
4.4	Tabulation data for relative angle of the right knee of the Tekong during pre-serve phase	74
4.5	Tabulation data for relative angle of the left knee of the Tekong during pre- serve phase	77
4.6	Biomechanical analysis summary data	79
4.7	Mean and standard deviation for joint displacement per joint of 'Jurus Satu' for sample 1 taken from set 1	90
4.8	Mean and standard deviation for joint velocity per joint of 'Jurus Satu' for sample 1 from set 1	91
4.9	Mean and standard deviation for joint acceleration per joint of 'Jurus Satu' for sample 1 from set 1	93
4.10	Average mean of displacement between two samples and its difference	94
4.11	Average standard deviation of displacement between two samples and its difference	95
4.12	Average mean of velocity between two sample and its difference	96
4.13	Average standard deviation of velocity between two samples and its difference	97

4.14	Average mean of acceleration between two samples and its difference	98
4.15	Average standard deviation of acceleration between two samples and its difference	98



## LIST OF FIGURES

2.1	Comprehensive methods to qualitative analysis (Bartlett, 2007).	8
2.2	Types of motion capture systems.	9
2.3	Kinect sensor (Microsoft, Kinect for Windows, 2015).	10
2.4	Kinect sensor component (Microsoft, Inside the Newest Kinect Kinect for Windows SDK – Infrared Control, 2015).	11
2.5	Depth Space Range (Microsoft, Coordinate Spaces for Kinect, 2015).	12
2.6	Skeleton Space Coordinates (Microsoft, Coordinate Spaces for Kinect, 2015).	13
2.7	Stem plot of RMS errors for x coordinates (a), y coordinates (b), and z coordinates (c). ‘x’ represent discarded data points while ‘o’ indicates points remained in the final 3D capture volume (Dutta, 2011).	14
2.8	Kalman filter result of knee angles (Jun, et al., 2013).	15
2.9	Marker placement on the limb (Gao, Cordova, & Zheng, 2012).	16
2.10	Effect of interference of multiple Kinect. First row (single Kinect) showed that some of the subject’s arms could not be tracked (yellow lines). Second and third row (four Kinects) model is fit to the depth silhouettes (fourth and fifth row), showing the (Berger, Ruhl, Schroeder, & Bruemmer, 2011).	16
2.11	User testing the interaction system. (Caon, Tscherrig, Mugellini, & Khaled, 2011).	17
2.12	3D model with estimated skeleton (Ye, et al., 2012).	18
2.13	Kinect skeleton data.	19
2.14	Standard court dimension by International <i>Sepak Takraw</i> Federation (ISTAF) (International <i>Sepak Takraw</i> Federation, 2013).	21
2.15	Triangle shape form from three joints.	22
3.1	Flowchart of study.	26

3.2	Design of duplex Kinect system.	27
3.3	Positioning of Kinect sensors (Baek & Kim, 2015).	28
3.4	Re-centered data set A and B.	31
3.5	Joints selection of skeleton from camera 1( $K_A$ ) to match the corresponding joints in camera 2( $K_B$ ).	32
3.6	Aligned and merged model of the skeleton.	32
3.7	Overview of the system.	34
3.8	A frame of merged skeleton from MATLAB.	35
3.9	SDK visualization on laptop screen.	35
3.10	Skeleton joints detected by Microsoft SDK and MatLab.	36
3.11	Subject and Kinect sensor operative measuring range (iPiSoft Wiki, 2014).	37
3.12	Project flowchart for Sepak Takraw Pre-serve experiment.	40
3.13	Planned experiment setup.	42
3.14	Kinect Xbox 360° experimental setup.	45
3.15	Example of sample (Tekong) performing serve action.	46
3.16	Example data of joint motion in x, y and z direction retrieval from Kinect software.	48
3.17	Experimental workflow for Silat experiment.	52
3.18	“Jurus Satu” (chulahitam.blogspot.my, 2011).	53
4.1	(a) Joints in indices return by Kinect sensor in SDK. (b) Order of the joints returned by Matlab.	58
4.2	Physical measurement on body by using a ruler.	59
4.3	Graph of bone length of joint shoulder left and elbow left.	61
4.4	Graph of length from shoulder right to elbow right.	62
4.5	Graph of length from elbow left to wrist left.	62
4.6	Graph of length from elbow right to wrist right.	64
4.7	Graph of length from shoulder center to spine.	64
4.8	Foot-to-foot Euclidean distance at pre-serve stage	66
4.9	3D relative angle for right knee, A at extension (pre-serve phase).	66
4.10	3D relative angle for left knee, B at extension (pre-serve phase).	67
4.11	Pre-serve or extension motion of the Tekong. (Hamdan et al., 2012)	67

4.12	Simplified skeleton model constructed by MATLAB software.	68
4.13	Graph of Foot-to-foot Euclidean, $d$ (m) distance vs speed of the ball graph, $s$ (km/h).	71
4.14	Example motion pattern of serve 1 attempt on right foot joint.	72
4.15	Graph of Relative angle for right knee, $A$ ( $^{\circ}$ ) at pre-serve phase (extension) vs ball speed, $s$ (m).	75
4.16	Example motion pattern of serve 1 attempt on left foot joint.	76
4.17	Graph of Relative angle for left knee, $B$ ( $^{\circ}$ ) at pre-serve (extension) vs ball speed, $s$ (m).	78
4.18	Graph of knee angle $^{\circ}$ vs attempt, $n$ .	81
4.19	Starting stance before the 'jurus' execution. (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	84
4.20	Anticipation to punch. (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	84
4.21	Initial stance of 'jurus satu'. (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	84
4.22	Right Hand parry (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	84
4.23	Forward lunge and backhand punch forward (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	85
4.24	Grappling posture with left leg up (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	85
4.25	Left hand parry with right hand fist clenched (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	85
4.26	Elbow uppercut forward. (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	85
4.27	Side kick forward (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained)	86

4.28	Forward right front (Middle image shows the actual elbow to the execution of the movement and right shows the simulation of the data obtained).	86
4.29	Anticipating an attack before to the next movement (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	86
4.30	Anticipation and taunt stance (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	86
4.31	Anticipating an attack from the side and sneak attack using right foot (Middle image shows the actual execution of the Movement and right shows the simulation of the data obtained).	86
4.32	The end of execution of 'jurus satu'. (Middle image shows the actual execution of the movement and right shows the simulation of the data obtained).	87
4.33	Graph shows the movement of subject 1 with time period of every "bunga silat" taken from set 1.	88
4.34	Graph shows the movement of subject 2 set 1 with time period of every "bunga silat" taken from set 1.	88
4.35	Graph shows the joint displaced per frame for subject 1 taken from set 1.	89
4.36	Graph shows the joint velocity per frame for subject 1 taken from set 1.	91
4.37	Graph shows the joint acceleration per frame for subject 1 taken from set 1	92
4.38	The right parts of body were hidden by the main body so that the position of those parts were estimated to incorrect places.	100
4.39	The length of both arms that have a significant and variable difference.	100
4.40	Vicon equipment setup during the experiment.	101
4.41	Duplex Kinect setup during the experiment.	102
4.42	Example of Vicon model using markers. (Merriault, et al., 2017)	102
4.43	Simplified skeleton model using Duplex Kinect Camera that constructed by MATLAB software	103

## LIST OF SYMBOLS AND ABBREVIATIONS

<i>3D</i>	-	Three-dimensional
<i>ACL</i>	-	Anterior cruciate ligament
<i>APIs</i>	-	Application program interfaces
<i>FOV</i>	-	Field of view
<i>Fps</i>	-	Frame rate per second
<i>GUI</i>	-	Graphical user interface
<i>ICP</i>	-	Iterative closest point
<i>IDE</i>	-	Integrated development environment
<i>km/h</i>	-	Kilometer per hour
<i>m</i>	-	Meter
<i>MATLAB</i>	-	Matrix laboratory
<i>SDK</i>	-	Software Development Kit
<i>PaA</i>	-	Plug-and-Access
<i>UTHM</i>	-	Universiti Tun Hussein Onn Malaysia
<i>V1</i>	-	Version 1
<i>V2</i>	-	Version 2

**LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
A	Skeletal data from Kinect Sensor	113
B	The bone length via MATLAB and SDK	114
C	Motion Capture Experimental Setup	118
D	Pre-serve motion captured by Kinect for 15 serves.	119
E	Silat data, displacement, velocity and acceleration (Subject 1)	124
F	Silat data, displacement, velocity and acceleration (Subject 2)	141
G	Graph both subject, displacement, velocity and accceleeration	157
H	Vitae	163



## CHAPTER 1

### INTRODUCTION

#### 1.1 Overview

Recently, biomechanical analysis is applied in many applications especially in biomedical, rehabilitation, sports and ergonomics. Such analyses are proven resulted in great impact on sports researches. Advance in sports science has achieved remarkable results in recent years. In athletics for instance, biomechanical analysis via biomechanical technology using imaging technology has succeeded in producing world champion athletes. (Curran & Frossard, 2012).

Biomechanics is an application of mechanical laws to living structure, specifically to human locomotion system (Garner, 2003). Biomechanics branches out from the root words; *bio* which means life or living organisms and mechanics which means the study of the action of forces on particles and mechanical systems. The biomechanics role in life is to grasp the concept of mechanical cause-effect relationships that determine the living organism's motion. Biomechanical analysis is used for maintaining physical functions, improving musculoskeletal health, improving mobility, product design and forensic biomechanics.

Sports biomechanics is a branch of biomechanics that underlines the comprehension of athlete's motion in sporting event through measurement, mathematical modeling and simulation. In sports, analysis is important to improve the performance of an athlete in a sport that they are best at. For an example, a football player shall precisely kick a ball in order to get the ball into a direction that he wanted by analyzing his body movement. Such analysis was made by applying biomechanics

understanding to the action which then to enhance and improve athlete's performance. With biomechanical analysis, analysts, coaches and trainers are able to improve athlete's performances and as well may reduce the probability of injuries and also improve rehabilitation.

## 1.2 Background of Study

The purpose of this study is to develop duplex motion capture system for sports biomechanical analysis. The visual sensor used in this motion capture system consists of two duplex Kinect sensors. It is where 'duplex' term is originally used.

Duplex Kinect sensor with in-house developed algorithm makes quantitative analysis possible. To produce the best analysis, accuracy between software developed in MATLAB platform and Software Development Kit (SDK) by Microsoft have been considered.

This study is intended to improve sports performance by the used of this developed motion capture system. "Bunga silat" in Silat and *sepak takraw* pre-serve were chosen as the case studies to justify the feasibility of this system. For *sepak takraw*, the motion analysis will provide the guide towards better pre-serve technique in order to improve athlete's performance while serving the ball. At the end of this study, the result obtained may provide improvement solution in the form of physical motion and increasing the effectiveness of *Sepak takraw* serve. The kinematic data analysis will describe the motion technique at pre-serve phase. In addition, this study also examined the capability of Kinect Xbox 360° sensor and software to be used in biomechanical analysis.

## 1.3 Problem Statement

The Ministry of Youth and Sports (Malaysia) has a mission to bring national sports to the highest level. In modern sports, sport sciences have significantly contributed to the top-class athletes. In recent years, introduction of depth camera used in motion capture have caught a massive attention by both researchers and biomechanists. In the past, such technology was not an option equipment in assisting the achievement of athletes, but now it is the opposite scenario. Therefore, the high-

performance sports certainly require motion capture technology to compete with others competitors.

Thus, a study involving quantitative analysis is important to obtain a more precise and accurate analysis. The existing commercially motion capture systems however have very limited features and not dedicated for the needs of our local athletes. The technology require markers to be attached on subject's body. Hence, physical movement is interrupted. In contrast, this research focused on the use of depth cameras as capturing sensor which does not involve markers. The Kinect sensor offers new perspectives for the development and application of affordable, portable and easy-to-use marker-less motion capture (MMC) technology. Although there have been some previous works done on biomechanical analysis using only single Kinect sensor, occlusion and self-occlusion tracking problems incurred. With the usage of duplex Kinect sensors, the mentioned limitation could be significantly reduced.

#### 1.4 Objectives

This project embarks the following objectives:

- i. To complete a duplex depth camera motion capture system for sports biomechanical analysis.
- ii. To build biomechanics motion analysis software using MATLAB coding platform and (Software Development Kit) SDK.
- iii. To prove the performance of the developed biomechanics motion analysis software via study on individual athlete in *sepak takraw* and silat.

## 1.5 Scope

The scope of this study

- i. Duplex Kinect Sensor by Microsoft is used as the motion sensor.
- ii. Only individual athlete is analyzed at any single time.
- iii. MATLAB coding platform and SDK are used as data capturing tools.
- iv. “Bunga Silat” technique in *Sepak Takraw Tekong* and silat are used as sample case studies for biomechanical analysis.

## 1.6 Significance of Study

Another substantial feature of the Kinect sensor is that it does not required any marker to be attached to the subject – a marker-less motion capturing system. The Vicon system usually used in motion capture technology in contrast requires reflective markers to be attached on the subject’s body, the time spent on attaching the markers to the subject is definitely not an advantage. Thus, with the use of duplex Kinect sensor, it could facilitate the set-up process and phase out complex equipment set-up. Besides, the size of the duplex motion capture system increases the portability and mobility as compared to lab based system such as Vicon. The fast, low cost, portable system for capturing these biomechanical measures would facilitate the biomechanists or researchers to bring their work task to the athlete instead of bringing the subject into the lab. This will bring the research work to a whole new advanced level of the way biomechanical analysis is done.

After the motion data extracted from the system, biomechanics analysis is used to assess the performance of athletes in order to gain a greater understanding of human movement. Thus, appropriate quantitative solutions could be developed to improve athlete’s techniques and thereby increase the performance, minimizing injuries and in turn, promoting career longevity.

A biomechanics researcher uses quantitative biomechanical analysis methods to discover new techniques, which communicated to the teachers and coaches who will implement them (McGinnis, 2013).

## **CHAPTER 2**

### **LITERATURE REVIEW**

#### **2.1 Introduction**

The purpose of this chapter is to review on previous studies that had been accomplished among other researchers in order to obtain more information that related to this project. It is important to study the existing research on biomechanical analysis within motion capture system. By reviewing the previous thesis, journals, articles and reports, considerably it provides important knowledge and information to this project.

#### **2.2 Biomechanics**

Biomechanics is the branch of science concerned with comprehension of the interrelationship of structures and functions of living beings, with referring to the kinetics and kinematics of motion (Adrian & Cooper, 1995). With the two components, kinematics and kinetics, the study can yield intensive comprehension on the factors affecting human body at rest or in motion. Biomechanics involves many other scientific disciplines. In order to fully comprehend human movement, the association of aspects like the study of work and energy in physics, forces and moments in mechanical engineering, and neuromuscular connections from biology is needed.

In specific, sport biomechanics study the effects of forces and motion mainly on sport performance. According to Bartlett (2007), sport biomechanics could be briefly defined as “the study and analysis of human movement patterns in sport”. Once

the movement patterns of an athlete is determined, coaches can analyze the sport movements of the athlete, select the best training exercises for him or her, in the meantime reduce or prevent the possibilities of injuries, as well as design or choose the sport equipment that best matches athletes' personal needs and eventually maximize economy and efficiency of movements. The use of technology makes it possible for coaches to provide the athletes with best possible opportunities to achieve maximal performance (Adegbesan & G.A., 2004)

### **2.2.1 Kinematics and Kinetics Motion**

Kinematic describes motion, including the pattern and speed of movement sequencing by the body segments, which often translate to the degree of coordination an individual display, while kinetic study the actions of forces associated with motion (Hall, 1999).

Sport kinematics analysis studies the positions, angles, velocities and accelerations of body segments and joints during motion, while kinetic analysis studies forces that produce the movement (Hay, 1993).

In brief, kinematics are a description of movement and do not consider the forces that cause that movement and the study of kinetics begins to answer the 'how and why' of the observed movement. However, as defined in the scope of study, only the kinematics motions of subject were analyzed in this research work.

### **2.3 The Concept of Biomechanical Analysis**


Biomechanical analysis is the evaluation of motion analysis techniques (Adrian & Cooper, 1995). Biomechanical analysis in sports involves both qualitative and quantitative analysis. When it comes to the sport biomechanics, it could be divided into three: qualitative; semi-quantitative and; quantitative analysis. Semi-quantitative mostly is the combination of qualitative analysis and some basic and common measurements, for example, joint angle of a motion, notation – goals scored, passes, etc.

### 2.3.1 Qualitative Analysis

Qualitative analysis depicts movements in non-numerical way, by expressing any movements as 'patterns'. Such analysis might appear to be very subjective due to the described 'data'. Thus, the reliability and accuracy of such data is very subjective especially when it is obtained in a competition. This type of analysis is applied more in structured and multidisciplinary approach (Bartlett, 2007). Qualitative analysis can only be provided successfully by individuals who have an excellent understanding of the specific sport or exercise movements and who can cooperate with a particular client group. Such cooperation requires a positive, ongoing commitment by the individuals involved (Payton & Bartlett, 2008). Qualitative analysis itself consists of four 'principles' proposed by several authors. The four methods are:

- i. Categorizing movement by its function;
- ii. Core notion of kinesiology;
- iii. Movement principles approach and;
- iv. Comprehensive approach to qualitative analysis

However, it is widely known that the most convincing approach in qualitative analysis of sports biomechanics is the comprehensive approach which was proposed by Knudson and Morrison (2002) as shown in Figure 2.1.





## REFERENCES

- Adegbesan, O., & G.A., E. (2004). The role of information technology in sports and physical education. *Multi-Disciplinary Approach-to Human Kinetics and Health Education*, 402-407.
- Adrian, M., & Cooper, J. (1995). *Biomechanics of Sports* (2nd ed.). Missouri: McGraw-Hill.
- Baek, S., & Kim, M. (2015). Dance Experience System Using Multiple Kinects. *International Journal of Future Computer and Communication*, Vol. 4, No. 1.
- Bartlett, R. (2007). *Introduction to Sports Biomechanics Analysing Human Movement Patterns*. Oxford: Routledge.
- Berger, K., Ruhl, K., Schroeder, Y., & Bruemmer, C. (2011). Markerless motion capture using multiple color-depth sensors. *Proceedings of Vision, Modeling and Visualization (VMV)*, 317-324.
- Besl, P. J., & McKay, N. (1992). A Method for Registration of 3-D Shapes. *IEEE Trans. on Pattern Analysis and Machine Intelligence (Los Alamitos, CA, USA: IEEE Computer Society)* 14 (2), 239-256.
- Bonnechère, B., Jansen, B., Salvia, P., Bouzahouene, H., Omelina, L., Cornelis, J., . . . Jan, S. V. (2014). Can the Kinect™ sensors be used for motion analysis? *Transaction On Electrical And Electronic Circuits And Systems*, Vol. 4(1), 1-6.
- Caon, M., Tscherrig, J., Mugellini, E., & Khaled, O. A. (2011). Context-Aware 3D Gesture Interaction Based on Multiple Kinects. *First International Conference on Ambient Computing, Applications, Services and Technologies (AMBIENT)*, 7-12.
- Curran , S. A., & Frossard, L. (2012). Biomechanical analyses of the performance of Paralympians: From foundation to elite level. *Prosthetics and Orthotics International*, 36(3), 380-395.<http://doi.org/10.1177/0309364612453257>
- Dutta, T. (2011). Evaluation of the Kinect Sensor for 3D Kinematic Measurement in the Workspace. *Applied Ergonomics* 43(4), 645-49.

- Esteves, A. C., Cunha, D., Reis, D. O. S., Giovana, S., & Santos, D. O. S. (2016). Impact and time of impact in bandal tchagui kick of the taekwondo, (January 2006), 2006–2009.
- Gao, B., Cordova, M., & Zheng, N. N. (2012). Three-dimensional joint kinematics of ACL-deficient and ACL-reconstructed knees during stair ascent and descent. *Human movement science* 31(1), 222-35.
- Garner, B. (2003). Joint Anatomy and Basic Biomechanics. *Joint Antomy*, 568.
- Hall, S. (1999). *Basic Biomechanics* (3rd ed.). Toronto: McGraw-Hill.
- Hamdan, N., Suwarganda, E., & Wilson, B. (2012). Factors Correlated with Sepak Takraw Serve Speed. *30th Annual Conference of Biomechanics in Sports*, (186), 413–416.
- Hay, J. (1993). *The Biomechanics of Sports Techniques* (4th ed.). Englewood Cliffs: Prentice Hall.
- iPiSoftWiki. (2014). *User Guide for Dual Depth Sensor Configuration*. Retrieved at December 25, 2018, from from iPiSoft Wiki: [http://wiki.ipisoft.com/User\\_Guide\\_for\\_Dual\\_Depth\\_Sensor\\_Configuration](http://wiki.ipisoft.com/User_Guide_for_Dual_Depth_Sensor_Configuration)
- Jamal, F. (2009). An analysis on tekong services between two Malaysian tekong in World Championship 2009 (Unpublished report) National Sports Institute, Kuala Lumpur, Malaysia.
- Jun, S.-k., Zhou, X., Ramsey, D. K., & Krovi, V. N. (2013). A Comparative Study of Human Motion Capture and Computational Analysis Tools.
- Knudson, D., & Morrison, C. (2002). *Qualitative Analysis of Human Movement*. Illinois: Human Kinetics.
- LaBelle, K. (2011). *Evaluation of Kinect Joint Tracking For Clinical and In-Home Stroke Rehabilitation Tools*. Indiana.
- Layton, (1993), C. Reaction + Movement-time and Sidedness in shotokan karate students. *Perceptual and Motor Skills*, vol. 76, n. 3, p. 765-6. <http://dx.doi.org/10.2466/pms.1993.76.3.765>
- Merriau, P., Dupuis, Y., Bouteau, R., Vasseur, P., & Savatier, X. (2017). A study of vicon system positioning performance. *Sensors (Switzerland)*, 17(7), 1–18. <http://doi.org/10.3390/s17071591>

- McGinnis, P. (2013). *Biomechanics of Sport and Exercise With Web Resource and MaxTRAQ 2D Educational Software Access* (3rd ed.). Illinois: Human Kinetics.
- Microsoft. (2015a, November). *Inside the Newest Kinect for Windows SDK—Infrared Control*. Retrieved from Kinect for Windows Blog:
- Microsoft. (2015b, November). *Microsoft Kinect for Windows*. Retrieved from Microsoft: <https://dev.windows.com/en-us/kinect/hardware>
- Microsoft. (2015c, November). *Kinect for Windows*. Retrieved from Microsoft: <http://www.microsoft.com/en-us/kinectforwindows/purchase/default.aspx> <http://blogs.msdn.com/b/kinectforwindows/archive/2012/12/07/inside-the-newest-kinect-for-windows-sdk-infrared-control.aspx>
- Microsoft. (2015d, November). *Coordinate Spaces for Kinect*. Retrieved from Microsoft Developer Network: <https://msdn.microsoft.com/enus/library/hh973078.aspx#Depth>
- Microsoft. (2015e, November). *Visual Studio - Microsoft Developer Tool*. Retrieved at December 2019, from Visual Studio: <https://www.visualstudio.com/>
- Mohamad Razali, A., Saidon, A., & Pathmanathan, K. S. (2012). Visual Perception of Kuda and Sila Service. *Movement, Health and Exercise*, 1(1), 26–37.
- Mündermann, L., Corazza, S., & Andriacchi, T. P. (2006). The evolution of methods for the capture of human movement leading to markerless motion capture for biomechanical applications. *Journal of NeuroEngineering and Rehabilitation*.
- Newman, A. (2015). How Fast is Sepak Takraw Really. Retrieved from <http://www.sepaktakraw.org/how-fast-is-sepaktakraw-really/>
- Koh, M., Hin, T., & Sujae, I. H. (2006). 3D Kinematic Analysis of Kuda And Sila Service Technique. *International Symposium on Biomachanic in Sports Volume 2*, 2(July), 18–21.
- OpenKinect. (2015, November). *libfreenect*. Retrieved from GitHub: <https://github.com/OpenKinect/libfreenect>
- Payton, C. J., & Bartlett, R. M. (2008). *Biomechanical Evaluation Of Movement In Sport And Exercise*. Oxford: Routledge.
- Pinto Neto, O. and Magini, M. (2008) Electromyographic and kinematic characteristics of kung fu Yau-Man palm strike. *Journal of Electromyography and*

- Kinesiology, vol. 18, n. 6, p. 1047-1052. PMid:17499517. <http://dx.doi.org/10.1016/j.jelekin.2007.03.009>
- Raposo, C., Barreto, J., & Nunes, U. (2013). Fast and Accurate Calibration of a Kinect Sensor. *3D Vision - 3DV 2013, 2013 International Conference on*, 342-349.
- Rodrigues, SCP. and Rodrigues, MIK. (1984) Estudo de correlação entre tempo de reação e tempo de movimento no Karatê. *Revista Kinesis*, n. especial, p. 107-117.
- Ruan, M. H. (2014). Extrinsic calibration of 3d sensors using a spherical target. *Proceedings of the International Conference on 3D Vision*.
- Saltzberg, Jr., Hondzinski, J. and Flanders, M. (2001) Humans adapt the initial posture in learning a whole-body kicking movement. *Neuroscience Letters*, vol. 306, n. 1-2, p. 73-76. PMid:12434836. [http://dx.doi.org/10.1016/S0304-3940\(01\)01875-4](http://dx.doi.org/10.1016/S0304-3940(01)01875-4)
- Sharma, A., Agarwal, M., Sharma, A., & Dhuria, P. (2013). Motion Capture Process, Techniques And Applications. *International Journal on Recent and Innovation Trends in Computing and Communication*, 251 – 257.
- Shotton, J., Fitzgibbon, A., Cook, M., Sharp, T., Finocchio, M., Moore, R., . . . Blake, A. (2013). Real-Time Human Pose Recognition in Parts from Single Depth Images. *Communications of the ACM*, 116-124.
- Sidthilaw, S. (2000). Three dimensional kinematic analysis of the Sepak Takraw serve in 13th Asian Games. *Proceedings of the National Conference on Biomedical Engineering*.
- Viana, Ms., Andrade, A. and Belmonte, Ap. (2005) Tempo de reação, flexibilidade e velocidade de membros inferiores de atletas de tae kwon do. *Coleção Pesquisa em Educação Física*, n. 3, p. 198-201
- Wham, R. M. (2012). *Three-Dimensional Kinematic Analysis Using the Xbox Kinect*. Tennessee: University of Tennessee Honors Thesis Projects.
- Ye, G., Liu, Y., Hasler, N., Ji, X., Dai, Q., & Theobalt, C. (2012). Performance capture of interacting characters with handheld kinects. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 828-841.
- Yeung, K. Y., Kwok, T. H., & Charlie Wang, C. L. (2013). *Improved Skeleton Tracking by Duplex Kinects: A Practical Approach*. Hong Kong: Department

of Mechanical and Automation Engineering, The Chinese University of Hong Kong, Hong Kong.

